

3M™ K6 RJ45 Jacks



3M RJ45 K6 UTP Jack

Part of 3M Network Solutions, the K6 RJ45 jack range is the 3M Category 6/Class E Permanent Link* solution (ISO/IEC 11801, EN 50173 and TIA 568-C.2)

The K6 jack is a core product in the 3M system solution, which includes a comprehensive range of patch panels, sockets and faceplates, patch cords and cables.

The RJ45 K6 jack is available in three different formats:

- UTP
- FTP with drain wire
- STP 360° braid or foil connection

Applications

- IEEE 802.3 1GBASE-T
- IEEE 802.3at PoE +

Standards

- ISO/IEC 11801 Edition 2, Am 1-2
- EN 50173-1
- ANSI/ TIA/ EIA-568-C.2-2009
- IEC60512-99-01

Features

- Tool-less jack
- Re-usable
- Shallow depth, cable entry from top or bottom
- One-click tool-less design
- Accepts both solid conductors from AWG 26 to 22 and stranded conductors
- Integral shutter
- POE+ compliant

Benefits

- Easy and quick to install
- Fast reliable connection in record time: all 8 copper conductors are effortlessly wired in a single operation
- Quality of connection by design: not dependant on tool condition or operator skills, just listen for the click
- If a wiring mistake is made there is no need to use a new jack
- No time wasted waiting for another delivery
- Easier cable management
- Allows a wide range of cable routing options
- Can be used with low profile trunking and boxes
- Solutions for all levels of EMC protection using the same accessories means less training
- Compatible with many cables on the market and enables 'jack to plug' cables to be manufactured using stranded conductors (for use in open office architectures)
- Increased dust protection, especially during installation or in a dirty environment
- No additional shuttering required on faceplates
- Allows direct mounting into floor boxes
- Protects jacks in the patch panel
- Supports PoE plus applications according to latest IEEE standards.

Permanent Link certificates are available at our website WWW.3M.com/Telecom. Performance of the 3M Cat 6 jacks with cables that are not specified in the certificates should be verified prior to usage

Specifications

Features

- Tool-less connection of all eight wires at one time by closing the metal locking wings
- Wire holder is labelled with both 568A and 568B wire maps
- Single forked contacts
- Integrated shutter

Technical characteristics

Conforms to permanent link and channel performance parameters of Class EISO/IEC 11801, EN 50173 and Category 6 TIA 568 standards

Conductor diameter:

solid wires: 0,50 to 0,65 mm
stranded wires: 7 x 0,15 to 0,20 mm

Maximum diameter of

wire insulation: 1,6 mm

Lead through resistance: < 200 mΩ


Insulation resistance: > 500 MΩ

Protection contacts: 1,6 μm gold

Voltage Rating: 75 VDC (maximum)

Ordering Information

Ref. No.




3M™ RJ45 K6 UTP Jack, white, 8 contacts

Also available in blue, green, red, yellow, black, orange and almond

VOLOCK6U8 (bags of 8)

VOLOCK6UV (bulk)




3M™ RJ45 K6 FTP Jack, white, 9 contacts

Ninth point for grounding continuity

VOLOCK6F8 (bags of 8)

VOLOCK6FV (bulk)



3M™ RJ45 K6 STP Jack, white, 8 contacts

Metallic nose and tinned bronze cover, shielded by a reversible metal cover

Shipped with a cable tie

VOLOCK6S8 (bags of 8)

VOLOCK6SV (bulk)

Important Notice

The details contained in this literature have been carefully prepared from information available to 3M at the time of its production. However, it is not intended to be relied upon for purposes of product specification and you should contact your sales representative if specification details are required. Because of the wide variety of processes and conditions in which these products may be used, the user should first carry out tests to determine the suitability of the products for the particular use intended. All questions of warranty and liability relating to 3M products are governed by the selling 3M subsidiary's Terms of Sale subject where applicable to the prevailing law.
3M is a trademark of the 3M Company.



3M Telecommunications

Europe, Middle East & Africa

c/o 3M Deutschland GmbH

Carl-Schurz-Straße 1

41453 Neuss · Germany

Tel.: ++49 (0)2131 / 14-5999

Fax: ++49 (0)2131 / 14-5998

Internet: www.3MTelecommunications.com

Rights reserved to make technical alternations.

Ref.-Nr. 07-401-34300 Edition 06/2014