




### PRODUCT DESCRIPTION

- This Empty Patch Panel belongs to the barpa cabling system. It accepts connectors from category 6 to 6A, UTP and STP. Has a very special design with a rear cable retention system with adjustable mechanical adjustment, that promotes quick installation and fast termination, avoiding the traditional fastening system by cable tie. Includes tag holder with plastic protection for identification of RJ 45, also with earth connection. For Modular Keystone.



#### STANDARD CONFORMITY

EIA 19-inch

#### PHYSICAL CHARACTERISTICS

Chassis	Black Electrostatic Powder-Coated Steel: phosphor bronze with tin plating over nickel
Color	Black (RAL9005)
Plastic	Fire self-extinguish high impact plastic

#### ELECTRICAL CHARACTERISTICS

Contact Resistance (MΩ)	200
Insulation Resistance (MΩ Min 500V DC)	500
Withstand Voltage	DC 1000V AC 700V RMS 60Hz, 1min

#### ENVIRONMENTAL CONDITIONS

Operating Temperature (°C)	-10 to +60
Storage Temperature (°C)	-40 to +70


#### MECHANICAL SPECIFICATIONS

Color Code	TIA/EIA 568A (international) and 568B (AT&T Standard) Wiring For Easy Installation
IDC Contacts - Solid Cable	Accept 22-24 AWG solid with a insulation diameter of 0.55-0.45 mm
IDC Contacts - Stranded Cable	Accept 22-26 AWG stranded with a insulation diameter of 0.76-0.48 mm
Insertion Life	750 times plugging
Plug Inforce (N)	< 30
Cable OD (mm)	5.0 - 8.5
Contact	Phosphor bronze with 4-6μ" gold plating

### • ORDER INFORMATION

Code	Description	Unit Weight (kg)	Inner Box		Carton		EAN Code
			Size (mm)	Quantity (un)	Size (mm)	Quantity (un)	
82230101124	Empty Patch Panel 24P 1U	0.46	505x120x55	1	520x260x300	10	5608445005151

### TECHNICAL DRAWING (mm)



As part of our goal to achieve quality excellence, our barpa System Warranty can give you 25 years products and solution assurance of compliance with the industry performance standard comparing with the class installed. This warranty applies to network infrastructure installations that was made by an approved barpa partner using an barpa solution (end-to-end). For more informations go to our website.

This document is authored and owned by barpa. It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice. The pictures/ drawings are merely illustrative.

More information: [info@barpa.eu](mailto:info@barpa.eu) or in [www.barpa.eu](http://www.barpa.eu)